

Ø45 fire hose cabinet of 15 and 20m P6415 / 20





Fire hose cabinet Ø45 mm according to EN 671-2 standard with 15 m (P6415) or 20 m (P6420) of plane hose manufactured according to UNE 23.091/2A. It is composed of:

Horizontal cabinet built of 1 mm steel plate thickness, painted in red RAL 3000, measures $640 \times 500 \times 160$ mm, with semi-blind door for polystyrene, and easy-open lock, provided with support arm fixing and preholes for water supply, including reel, hose, nozzle, swing arm, seat valve, manometer and supply hose.

It can be made in another color, with the RAL provided by the costumer, or in stainless steel, and it can be mounted in a floor bow.

Likewise, under command, the door design has some options: standard, red blind, white blind, white semi-blind, totally stainless, etc.

Features:

- Reeling frame with Ø350 mm.
- Plane hose of Ø45 mm and 15 or 20 m length, manufactured according UNE 23.091/2A and CE mark, with adaptors manufactured according UNE 23.400 of Ø45, slight use.
- Seat valve at 120° output, made of brass, with threads of 1 ½" and adaptor according to UNE 23.400, slight use.
- Manometer graduated from 0 to 25 bars.
- Hose nozzle of three positions: close, spray and jet, connected to the end of the hose by slight use adaptors.

